

Emirates Extruded Polystyrene LLC

P. O. Box 28807, Dubai, United Arab Emirates Tel: +971 4 8850471 Fax: +971 4 8853920 Email: info@eepdubai.com

REF. NO.: EEP/GM/20150219/02

DATE: 19/02/2015

INSTRUCTIONS FOR STORAGE

Manufacturer

Emirates Extruded Polystyrene LLC Product Extruded Polystyrene boards for thermal insulation

Brand Standard

E-FOAM, Extruded Polystyrene Foam Board, thermal insulation Bear the below mentioned standard values as per ASTM C 578 b12.

Description

25 mm to 100 mm thick with density of 30-50 KG/M3

Color

Apple green

Installation

E-FOAM square edge insulation boards are easy to handle cut and install. The square edge boards are designed to ensure energy efficiency and minimize on site cutting process and wastage. For installation, use polystyrene compatible adhesive glue to hold the boards firmly in place during fixing. It is highly recommended to remove irregular masonry or surface on the foundation wall or slab prior to installation. Below grade walls should be protected from moisture leakage and dampness prior to installation of E-FOAM insulation. Approved drainage system should be installed to ensure to meet local codes and regulations. E-Foam insulation sheets must be installed at the same time when entire system is ready otherwise installing the E-Foam insulation boards open to direct sun light/heat will damage thermal properties and sheets may bend if exposers to sun light/heat continued for longer period

Storage

E-FOAM thermal insulation boards should be stored in covered area with clean flat surface free from flammable materials and good ventilation to be maintained. If stored outside, then E-Foam should be protected from direct sunlight away from flammable source, covered with bright colored UV protection plastic sheets properly anchored down against high winds.

For Emirates Extruded Polystyrene LLC

Mallikarjuna General Manager





